

## TECHNICAL DATA SHEET

### **AMALIE XLO Ultimate Molybdenum Fortified CK-4/SN 10W-40**

(May 2021 edition)

AMALIE XLO Ultimate Synthetic Blend Molybdenum Fortified CK-4/SN 10W-40 is premium high-performance diesel engine oil utilizing the latest in engine oil additive technology and a blend of quality conventional and synthetic base stocks to offer the ultimate protection of your engine. It is designed to meet or exceed the latest OEM and API CK-4 requirements AMALIE CK-4/SN 10W-40 also meets API SN classification for use in gasoline engines and is an excellent choice for operators with mixed fleets. This oil is specially designed to protect EGR/Low-Emission Diesel Engines while maximizing the durability of Diesel Particulate Filters (DPF's).

AMALIE XLO Ultimate Synthetic Blend Molybdenum Fortified CK-4/SN 10W-40 is recommended for use in a wide range of heavy-duty applications and operating environments found on-and off-highway, including engines operating under heavy loads. It is formulated for extended service/extended drain when operated under typical operating conditions. AMALIE CK-4/SN 10W-40 offers improved TBN retention, lower oil consumption, greater wear protection, oxidation stability, excellent shear stability, and reduced high temperature deposits.

#### Benefits:

- High Soot Handling.
- Improved Sludge Control.
- > Excellent Protection for Metal Components from Rust, Corrosion and Wear.
- Superior Oxidation Stability.
- Shear Stable Formulation.
- One Oil for Mixed Fleets.
- Exceptional Oil Consumption Control.
- Lasting TBN Retention.

Typical	Physical	and	Chemical	<b>Properties</b>
i v bicai	ıııvəicai	anu	CHEIIIICAI	1 100011103

Kinematic Viscosity @100°C, cSt	15.20
Kinematic Viscosity @40°C, cSt	.98.75
Viscosity Index	160
Flash Point, °C (°F)	215(419)
Pour Point, °C (°F)	33(-27.4)
Density, S.G	0.8704
Sulfated Ash, Wt%	0.95
TBN, mgKOH/g	10.0

Typical values are listed. Variations not affecting the performance of this fluid may occur during production however; these variations will not fall outside of set specification parameters.



# TECHNICAL DATA SHEET

## AMALIE XLO Ultimate Molybdenum Fortified CK-4/SN 10W-40

pprovals and Recommendations SPECIFICATIONS	AMALIE 10W-40	
ACEA:		
E9, E7		
Allison		
TES 439		
API:	\\	
CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4		
SN, SM, SL, SJ	V	
Caterpillar		
ECF-3, ECF-2	$\sqrt{}$	
Cummins:		
CES 20086, CES 20081		
Daimler (MB)		
MB 228.31	$\sqrt{}$	
Detroit Diesel		
DFS 93K222, 93K218	V	
Ford		
WSS M2C171-F1	V	
Global		
DHD-1	V	
JASO		
DH-2, DH-1	V	
Mack		
EOS-4.5, EO-O Premium Plus, EO-N	V	
MAN		
M 3575	V	
Mil-PRF		
2104 Rev. H	V	
MTU		
2.1	V	
Navistar		
TSI-99-12	V	
Renault		
RLD-4, RLD-3	V	
Volvo		
VDS-4.5, VDS-4, VDS 3	V	

Please consult Amalie Technical Services or your local representative for a full listing of applications.